



Recommended tool

HERO
8.0



	L mm.	E mm.	mm.	D mm.	d mm.	S mm.	N.	Nn.	Codice Code
M4	11,5	1,5 - 3,5	ø 6,0	5,9	8,5	1,5	6.800	3,0	BTR04115CKKNS
M5	13,5	1,5 - 4,0	ø 7,0	6,9	9,5	1,5	10.000	6,0	BTR05135CKKNS
M6	16,0	1,5 - 4,5	ø 9,0	8,9	11,5	1,5	15.000	10,0	BTR06160CKKNS
M8	19,0	1,5 - 4,5	ø 11,0	10,9	13,5	1,5	27.000	24,0	BTR08190CKKNS
M10	21,0	1,5 - 4,5	ø 13,0	12,9	15,5	1,5	37.000	48,0	BTR10210CKKNS

INSERTO FILETTATO CILINDRICO RULLATO APERTO RIVET NUT CYLINDRICAL GROOVED OPEN END

Descrizione:

Adatto per applicazioni con un unico accesso. Il corpo rullato garantisce una presa più forte di fissaggio che offre una resistenza di lunga durata.

La sua particolare forma impedisce il corpo di roteare.

Si consiglia per applicazioni su tubi, elementi ad estrusione, fogli metallici e plastica.

Disponibile nelle seguenti forme:

• Testa Piana • Testa Svasata • Testa a Filo

E nelle seguenti versioni:

• Acciaio • Alluminio • Inox

Description:

Suitable for application of one size access. The grooved body assures a stronger grip of fastening that offers a more resistant and long lasting fixing as its particular shape prevents the body from rotation. It is recommended for applications as tubes, extrusion, metal sheets and plastic.

Available in the following shapes:

• Flat Head • Countersunk Head • Reduced Head

And in following versions:

• Steel • Aluminium • Stainless Steel A2