



 Testa a Filo
Cilindrico Rullato Aperto
INOX A2



 Reduced Head
Cylindrical Grooved Open End
STAINLESS STEEL A2



Recommended tool

 **HERO**
8.0



Cilindrico
Cylindrical

TSKNi2

	L mm.	 E mm.	 mm.	D mm.	d mm.	S mm.	 N.	 Nn.	Codice Code
M3	9,0	0,5 - 2,0	ø 5,0	4,9	6,0	0,5	4.000	1,2	BTR03090TSKNi2
M4	10,0	0,5 - 3,0	ø 6,0	5,9	6,5	0,5	6.800	3,0	BTR04100TSKNi2
	12,5	3,1 - 4,0							BTR04125TSKNi2
M5	11,5	0,5 - 3,0	ø 7,0	6,9	7,5	0,5	10.000	6,0	BTR05115TSKNi2
	13,0	3,1 - 4,0							BTR05130TSKNi2
M6	14,0	0,5 - 3,0	ø 9,0	8,9	9,5	0,5	15.000	10,0	BTR06140TSKNi2
	17,5	3,1 - 5,0							BTR06175TSKNi2
M8	15,5	0,5 - 3,0	ø 11,0	10,9	11,5	0,65	27.000	24,0	BTR08155TSKNi2
	19,5	3,1 - 5,0							BTR08195TSKNi2
M10	19,5	0,5 - 3,5	ø 13,0	12,9	13,5	0,7	37.000	48,0	BTR10195TSKNi2
	23,0	3,1 - 6,0							BTR10230TSKNi2



Il valore del TAGLIO varia a seconda della superficie, della dimensione e del materiale delle viti.
The value of SHEAR varies depending on surface, dimension and material of screws.